



TM

VENIERI
SPA

PRODUCT LINE

LOADERS
TELESCOPIC WHEEL LOADERS
BACKHOE TOOL CARRIERS





New fully-equipped
plant opens.



Production
of **earthmoving
machines** begins.



Venieri introduces
the **world's first
hydrostatic transmission**
in earthmoving machines.



Actual
main plant
opens.



Production
of the **rigid type**
of Backhoe Loader
discontinued.



Installation of
**Hydrostatic
transmission** begins
in **all machines.**



75
Worldwide Partners
reached.



70th ANNIVERSARY.
QUALITY MEETS
HISTORY.



Complete **restyling**
of **Company main**
Headquarters.



1948 →

← 1954

1956 →

← 1960

1962 →

← 1968

1974 →

← 1980

1986 →

← 1992

1999 →

← 2002

2010 →

← 2012

2016 →

← 2018

2021 →

← 2023



Ferdinando and
Carlo Venieri
create the first
**Venieri crawler
tractor.**



Venieri starts
co-operation
with **Perkins** engine
manufacturer.



Production of
hydrostatic forklift
begins.



Venieri becomes a
Limited Company (L.T.D.)
strengthening his name
on the domestic market.



Introduction
of a **new type**
of **backhoe loader.**



Venieri patented the
world's **first electrical
backhoe loader.**



100%
Green Power
Company.



Venieri begins
introducing
TIER 4F engines.



Entire range
now featuring
TIER 4F engines.

WHEEL
LOADERS



13.63C



10.63D



9.63D



8.63C HL



7.63D

Linkage	"Z" BAR	PARALLEL	"Z" BAR	PARALLEL	"Z" BAR
Engine Max Power	184 HP	143 HP	143 HP	128 HP	128 HP
Engine Emission	TIER 4f - DPF + DEF	TIER 4f - DPF + DEF	TIER 4f - DPF + DEF	TIER 4f - DPF + DEF	TIER 4f - DPF + DEF
Breakout Force	26,455 lbs	17,637 lbs	18,960 lbs	20,723 lbs	20,062 lbs
Static Tipping Load, Full Turn	21,164 lbs	11,464 lbs	12,125 lbs	10,141 lbs	11,023 lbs
Bucket Capacity, Min/Max	3.5 - 3.9 cu/yd	2.3 - 2.9 cu/yd	2.3 - 2.9 cu/yd	1,6 cu/yd	1.8 - 2.6 cu/yd
Max Permissible Weight	31,195 lbs	22,289 lbs	22,289 lbs	19,290 lbs	19,290 lbs
Tyres	20,5 R25	17,5 x 25	17,5 x 25	460/70 R24	15,5 x 25
Forks Load Capacity (EN 474-3)	12,346 lbs	7,496 lbs	8,113 lbs	6,173 lbs	6,614 lbs
Max Speed	25 mph	25 mph	25 mph	25 mph	25 mph



5.63C



4.63H



2.63D Plus



1.63D



1.33C

Linkage	"Z" BAR	"Z" BAR	"Z" BAR	"VZPK"	PARALLEL
Engine Max Power	79 HP	72 HP	53 HP	53 HP	53 HP
Engine Emission	TIER 4f - ONLY MUFFLER	TIER 4f - DPF	TIER 4f - DPF	TIER 4f - DPF	TIER 4f - DPF
Breakout Force	14,110 lbs	12,346 lbs	11,685 lbs	8,466 lbs	5,071 lbs
Static Tipping Load, Full Turn	9,700 lbs	9,259 lbs	6,614 lbs	4,079 lbs	4,409 lbs
Bucket Capacity, Min/Max	1.4 - 2.0 cu/yd	1.3 - 2.0 cu/yd	1.0 - 1.6 cu/yd	0.65 - 1.0 cu/yd	0.6 cu/yd
Max Permissible Weight	13,823 lbs	13,669 lbs	10,582 lbs	7,937 lbs	9,105 lbs
Tyres	405/70 R20	16/70 x 20	12,0/75 x 18	12 - 16,5	12 - 16,5
Forks Load Capacity (EN 474-3)	5,997 lbs	5,644 lbs	4,233 lbs	2,434 lbs	2,646 lbs
Max Speed	25 mph	25 mph	17 mph	25 mph	12 mph

TELESCOPIC WHEEL LOADERS



8.63TL

Linkage	TELESCOPIC ARM
Engine Max Power	143 HP
Engine Emission	TIER 4f - DPF + DEF
Max Load Height with Forks - Telescopic Extended	17'4"
Bucket Capacity, Min/Max	1.6 cu/yd
Max Permissible Weight	20,062 lbs
Tyres	460/70 R24
Forks Load Capacity (EN 474-3)	7,055 lbs
Max Speed	25 mph



1.63D TL

Linkage	TELESCOPIC ARM
Engine Max Power	53 HP
Engine Emission	TIER 4f - DPF
Max Load Height with Forks - Telescopic Extended	12'2"
Bucket Capacity, Min/Max	0.65 cu/yd
Max Permissible Weight	8,818 lbs
Tyres	31X15,50 - 15,3
Forks Load Capacity (EN 474-3)	2,756 lbs
Max Speed	25 mph

BACKHOE TOOL CARRIERS



8.23G

Linkage	"Z" BAR	"Z" BAR
Engine Max Power	106 HP	106 HP
Engine Emission	TIER 4f - DPF + DEF	TIER 4f - DPF + DEF
Breakout Force	15,212 lbs	23,810 lbs
Static Tipping Load, Full Turn	11,574 lbs	13,558 lbs
Bucket Capacity, Min/Max	1.4 - 1.8 cu/yd	1.7 - 2.6 cu/yd
Max Permissible Weight	18,717 lbs	21,870 lbs
Tyres	16/70 x 24	17,5L x 24
Forks Load Capacity (EN474-3)	6,878 lbs	8,554 lbs
Max Speed	25 mph	25 mph
Max Digging Depth, Std./Telescopic	15'1" - 17'9"	16'5" - 19'8"

10.23E



1.33C

Linkage	PARALLEL
Engine Max Power	53 HP
Engine Emission	TIER 4f - DPF
Breakout Force	5,071 lbs
Static Tipping Load, Full Turn	4,409 lbs
Bucket Capacity, Min/Max	0.6 cu/yd
Max Permissible Weight	9,105 lbs
Tyres	12 - 16,5
Forks Load Capacity (EN474-3)	2,646 lbs
Max Speed	12 mph
Max Digging Depth, Std./Telescopic	9'0" - 10'8"



www.venieriamerica.com



vf_venieri



vfvenieri



vfvenieri



YouTube

VF Venieri



vf-venieri-spa



Via Piratello, 106 - 48022 Lugo (RA) - ITALY
Tel. +39 0545 904411 Fax +39 0545 30389
e-mail: info@vf-venieri.com | www.vf-venieri.com

Spare Parts

Tel. +39 0545 904429 Fax +39 0545 24555
e-mail: ricambi@vf-venieri.com