



TM

**VENIERI**  
SPA

**4.63H**  
**5.63C**

WHEEL LOADERS







#### 4K LINKAGE.

New completely redesigned linkage to the latest state of the art, for **maximum break-out force and interchangeability** with previous versions.



#### AUTO SAFETY IS OUR PRIORITY.

The **negative parking brake** is integrated into the front axle for maximum safety in all operative conditions *(optional on 4.63H)*.



#### SILENCE, PLEASE.

Thanks to the new sound proof technology and special "anti vibration" rubber shock absorbers it was possible to reach a **deeply noise reduction inside cabin, for maximum comfort** for the operator.



#### 360°

#### BREATHTAKING VIEW.

The new cabin design guarantees **360° visibility**, for **complete working control** on each attachment installed granted the best safety condition ever. Cabin level II ROPS/FOPS.



#### BE COOL.

The **brand new ventilation system** grants an high level of operator comfort. With **VENIERI CLIMATRONIC** or thanks to new technological Air-condition you can find the perfect Enviroment inside your cabin.



#### 100% VENIERI DESIGN.

In the new machines our **Venieri Design Lab** follows the "family feelings" but introduces significant **stylistic innovations**.



### TOTAL STABILITY.

Oscillating rear axle fixed to the frame with **maintenance-free** supports.



### TIER IVf ENGINE.

The new **Yanmar** and **Deutz** engines comply with the **latest emission standards** delivering **high torque** at low rpm.



AIR CYCLONE  
PRECLEANER

### ALWAYS CLEAN AIR.

The new air cleaner system offers a **two stage filtration**, through **high efficiency primary filters** and **safety filters**, that could be integrate with cyclon pre-filter (*optional on 4.63H*) for maximum engine protection.



### DOUBLE ATTENTION FOR FUEL SAVING.

The new electrically controlled **dual speed cooling fan**, adjusts the rotation speed according to the working conditions, **reducing fuel consumption and noise**.



### BUILT FOR POWER, DESIGNED FOR AGILITY.

The **special layout of the counterweight** grants **perfect maneuverability**, **maximum drive angle** and protection of the integrated rear lights in narrow spaces.

# 4.63H

WHEEL LOADER - "Z" LINKAGE



## DIESEL ENGINE

4 cylinder in line engine, common-rail injection with electronic control, exhaust gas recirculation, water cooled, dry filtration, particulate filter. Emissioned according to CE 97/68 - TIER IVf.

Type	Yanmar 4TNV98C
Max. power	53 kW - 72 HP
Rated rpm	2.500
Power ISO/TR 14396	51,7 kW - 70 HP
Power EEC 80/1269	51,7 kW - 70 HP
<b>Economic working range</b> (rpm)	1200 - 1600
Max torque	ft lbf 178
Bore	in 3.86
Stroke	in 4.33
Displacement	in³ 203



## ELECTRIC SYSTEM

Battery	12 Volt
Capacity	110 Ah - 850 A
Alternator rating	80 A
Reverse warning	Standard
Wiring accord to	IP 67 - DIN 40050



## TRANSMISSION

Hydrostatic transmission with automatic power regulation and closed circuit with pumps and variable displacement engine. Two speed fwd/rev, with single-lever electronic control.

Speed	Forward	Reverse
1 <sup>st</sup> gear mph	0÷7	0÷7
2 <sup>nd</sup> gear mph	0÷22	0÷22

2<sup>nd</sup> gear automatic selection available as optional



## AXLES

Two heavy duty equal size axles with planetary final drives in each wheel. Fixed rigid drive axle. Oscillation rear axle on rear chassis section up to a total angle of 25°. Transfer gearbox transferring movement directly to the rear and to the front axle via transmission shaft.

Self locking limited slip differential on front axle.

Self locking limited slip differential on rear axle (optional).



## BRAKE

Service: hydraulic multi-disc oil brake on front axle working on all the wheels.

Parking brake: mechanical operating on service brake.



## TYRES

Standard	16/70 x 20
Optional	405/70 R20 • 14.5 x 20



## STEERING

Servo-assisted steering **LOAD SENSING** system.

Total steering angle	80°
Inner tyres turning radius	ft in 8'5.77"
External tyres turning radius	ft in 14'9.76"
External bucket turning radius*	ft in 16'4.06"

\* Bucket on traveling condition



## HYDRAULIC SYSTEM

Two gear pump, the first for loader and steering circuit with **LOAD SENSING** valve, the second for the fan circuit with two rotating speed.

Modular two-element control valve with main relief valve. Double acting hydraulic cylinders.

Hydraulic oil cooling radiator.

Full flow oil filter on the return line.

Single lever arm to control 4 position lifting system and 3 position bucket system.

Max. flow	gpm	18.49
Max. flow with kit high flow (optional)	gpm	26.42
Loader relief valve pressure	psi	3,336
Steering relief valve pressure	psi	2,756
Lift cylinder	in	3.15x23.03
Bucket cylinder	in	3.35x15.55
Lifting time (full)	sec.	4.8
Lowering Time (empty)	sec.	3.7
Unloading Time	sec.	1.95
Total cycle time	sec.	10.45



## SERVICES CAPACITIES

Engine	gal	2.91
Front axle	gal	1.48
Rear axle	gal	1.53
Gear box	gal	3,8
Hydraulic circuit	gal	1
Brake circuit	gal	0.29
Fuel	gal	19.81
Water cooling	gal	3.96



## TECHNICAL FEATURES

Standard bucket capacity	yd³	1.31
Bucket width	ft in	6'6.74"
Straight static tipping load	lbs	10,141
Full turned tipping load	lbs	9,259
Lifting capacity at max. height	lbs	8,598
Hinge pin height	ft in	10'8.35"
Dump height at 41°	ft in	8'4.39"
Reach at 41°	ft in	2'2.57"
Breakout force	lbs	12,346





## DIMENSIONS AND WEIGHT

Max. lenght in transfer position	ft in	17'3.48"
Max. width in transfer position	ft in	6'6.74"
Tyre external width	ft in	6'1.74"
Track width	ft in	5'0.24"
Wheel base	ft in	7'5.57"
Ground clearance	in	12.99
Max height	ft in	9'0.66"
Standard operating weight	lbs	11,905
Max permissible weight	lbs	13,669


## dB NOISE LEVEL

Noise level inside cabin ISO 6396 - LpA	dB(A)	74
Exterior noise level ISO 6395 - LwA	dB(A)	98


**PERFORMANCE DATA**




**UNIVERSAL  
BUCKET**

**MULTI PURPOSE  
BUCKET**

**OVERSIZE**

**FORKS**

Full load bucket capacity (SAE)	yd <sup>3</sup>	1,31	1,18	1,96	/
Bucket width	ft in	6'6.74"	6'10.78"	7'4.58"	/
Bucket weight	lbs	772	1,102	1,102	/
Overall operating height, fully raised	ft in	13'5.42"	13'3.45"	13'7.58"	/
Forks lengthh (Standard)	ft in				3'3.37"
Forks lengthh (Optional)	ft in				3'11.24"
Hinge pin height	ft in	10'8.35"	10'8.35"	10'8.35"	/
Dump clearance	°	41°	41°	41°	/
Dump height	ft in	8'4.39"	8'3.41"	8'2.43"	/
Dump distance	ft in	2'2.57"	2'1.59"	2'4.54"	/
Max dump distance	ft in	4'8.1"	4'6.13"	4'10.07"	/
Bucket static tipping load, straight	lbs	10,141	10,582	9,590	/
Bucket static tipping load, full turn	lbs	9,259	9,700	8,818	/
Forks static tipping load, full turn	lbs				7,055
Payload EN 474-3 (80%) [•]	lbs				5,644
Payload EN 474-3 (60%) [•]	lbs				4,233
Breakout force	lbs	12,346	13,448	11,464	/
Total length	ft in	17'3.48"	17'1.51"	17'5.45"	/
External bucket turning radius	ft in	16'4.06"	16'2.49"	16'8.39"	/
Standard operating weight	lbs	11,905	12,236	11,905	/

[•] Center of gravity 19.69"

**POWER**

**TORQUE**

**FUEL CONSUMPTION**




# 5.63C

WHEEL LOADER - "Z" LINKAGE



## DIESEL ENGINE

4 cylinder in line, turbocharged, common-rail injection with electronic control, exhaust gas recirculation, water cooled, dry filtration, oxidation catalyst (DOC). Emissioned according to CE 97/68 - TIER IVf.

Type	Deutz TD 2.9 L4
Max. power	58 kW - 79 HP
Rated rpm	2.600
Power ISO/TR 14396	55,4 kW - 75 HP
Power EEC 80/1269	55,4 kW - 75 HP
<b>Economic working range</b>	rpm 1400 - 1800
Max. torque	ft lbf 260
Bore	mm 92
Stroke	mm 110
Displacement	in <sup>3</sup> 178



## ELECTRIC SYSTEM

Battery	12 Volt
Capacity	110 Ah - 850 A
Alternator rating	95 A
Reverse warning	Standard
Wiring according to	IP 67 - DIN 40050



## TRANSMISSION

Hydrostatic transmission with automatic power regulation and closed circuit with pumps and variable displacement engine. Gearbox with 2 mechanical selections: 2 work speeds (fwd/rev) and 2 road speeds (fwd/rev).

Work speed	Forward	Reverse
1 <sup>st</sup> gear mph	0 ÷ 2	0 ÷ 2
2 <sup>nd</sup> gear mph	0 ÷ 7	0 ÷ 7

Road speed	Forward	Reverse
1 <sup>st</sup> gear mph	0 ÷ 9	0 ÷ 9
2 <sup>nd</sup> gear mph	0 ÷ 25*	0 ÷ 25*

\* Self limited max. speed



## AXLES

Two heavy duty equal size axles with planetary final drives in each wheel. Fixed rigid drive axle. Oscillation rear axle on rear chassis section up to a total angle of 25°. Transfer gearbox transferring movement directly to the rear and to the front axle via transmission shaft. Self locking limited slip differential on front axle. Self locking limited slip differential on rear axle (optional).



## BRAKE

Service: hydraulic multi-disc oil brake on front and rear axles. Parking brake: negative hydraulic on front axle, electrically applied.



## TYRES

Standard	405/70 R20
Optional	455/70 R20 • 14.5 x 20



## STEERING

Servo-assisted steering **LOAD SENSING** system.

Total steering angle	80°
Inner tyres turning radius	ft in 8'5.77"
External tyres turning radius	ft in 14'9.76"
External bucket turning radius*	ft in 16'4.06"

\* Bucket on traveling position



## HYDRAULIC SYSTEM

Two gear pump, the first for loader and steering circuit with LOAD SENSING valve, the second for the fan circuit with two rotating speed. Modular two-element control valve with main relief valve. Double acting hydraulic cylinders.

Hydraulic oil cooling radiator. Full flow oil filter on return line.

Single servo lever arm control with 4 position lifting system and with 3 position bucket system.

Max. flow	gpm	23.78
Max. flow with high flow (optional)	gpm	31.7
Loader relief valve pressure	psi	3,336
Steering relief valve pressure	psi	2,756
Lift cylinder	in	3.35x22.83
Bucket cylinder	in	3.54x15.83
Lifting time (full)	sec.	4.38
Lowering Time (empty)	sec.	3.41
Unloading Time	sec.	1.9
Total cycle time	sec.	9.69



## SERVICES CAPACITIES

Engine	gal	2.11
Front axle	gal	1.37
Rear axle	gal	1.64
Gear box	gal	0.48
Hydraulic circuit	gal	18.49
Brake circuit	gal	0.53
Fuel	gal	19.81
Water cooling	gal	3.96



## TECHNICAL FEATURES

Standard bucket capacity	yd <sup>3</sup>	1.44
Bucket width	ft in	6'10.68"
Straight static tipping load	lbs	10,913
Full turned tipping load	lbs	9,700
Lifting capacity at max. height	lbs	9,149
Hinge pin height	ft in	11'0.28"
Dump height at 40°	ft in	2'1.98"
Reach at 40°	ft in	660
Breakout force	lbs	14,110




## DIMENSIONS AND WEIGHT

Max. lenght in transfer position	ft in	17'4.46"
Max. width in transfer position	ft in	6'10.68"
Tyre external width	ft in	6'4.26"
Track width	ft in	5'0.24"
Wheel base	ft in	7'5.57"
Ground clearance	in	12.99
Max. height	ft in	9'0.66"
Standard operating weight	lbs	12,787
Max. permissible weight	lbs	13,823


## dB NOISE LEVEL

Noise level inside cabin ISO 6396 - LpA	dB(A)	75
Exterior noise level ISO 6395 - LwA	dB(A)	99


**PERFORMANCE DATA**




**UNIVERSAL  
BUCKET**

**MULTI PURPOSE  
BUCKET**

**OVERSIZE**

**FORKS**

Full load bucket capacity (SAE)	yd <sup>3</sup>	1,44	1,18	1,96	/
Bucket width	ft in	6'10.68"	6'10.68"	7'4.58"	/
Bucket weight	lbs	882	1,102	1,102	/
Overall operating height, fully raised	ft in	13'9.35"	13'7.19"	13'11.32"	/
Forks length (Standard)	ft in				3'3.37"
Forks length (Optional)	ft in				3'11.24"
Hinge pin height	ft in	11'0.28"	11'0.28"	11'0.28"	/
Dump clearance	°	40°	40°	40°	/
Dump height	ft in	8'9.71"	8'8.69"	8'7.7"	/
Dump distance	ft in	2'1.98"	2'1"	2'3.95"	/
Max dump distance	ft in	3'2.58"	3'0.61"	3'4.55"	/
Bucket static tipping load, straight	lbs	10,913	11,354	10,362	/
Bucket static tipping load, full turn	lbs	9,700	10,141	9,149	/
Forks static tipping load, full turn	lbs				7,496
Payload EN 474-3 (80%) [●]	lbs				5,997
Payload EN 474-3 (60%) [●]	lbs				4,497
Breakout force	lbs	14,110	15,190	13,250	/
Total length	ft in	174.46"	17'9.58"	18'1.52"	/
External bucket turning radius	ft in	16'4.06"	16'2.49"	16'8.39"	/
Standard operating weight	lbs	12,787	13,007	12,787	/

[●] Center of gravity 19.69"

**POWER**

**TORQUE**

**FUEL CONSUMPTION**




# THE NEW CABIN


## A BREATHTAKING VIEW.

Take a seat in your customized control room. Create your ideal work space by **adjusting** the **pneumatic seat\*** and the **steering wheel** to suit your specific needs. Select the commands, **all at your fingertips**. Excellent **visibility to 360°** gives you the best view to work with maximum efficiency. The combination of **breathtaking cabin** and the **latest state of the art of 4K linkage** allows the **maximum control** of your attachments.

*\*Optional.*







In the new 5.63C and 4.63H cabin we **minimized "blind spots"** for **superb visibility** in all working conditions.

## OPEN SESAME!

The **door with double opening** allows the operator to work with the entrance door closed, with top glass opened, ensuring **maximum ventilation** even with the A/C off and **without protruding parts out of shape**.



# 5.63C


## BEAUTY FINALLY MEETS FUNCTIONALITY.

The Venieri Design Lab, with the 5.63C new cab tried to merge **function** and **style** with the aim of become the best in the market. The new interior design has also allowed us to create different compartments useful for storing small tools, mobile phone, beverage, and more.




## ARTIFICIAL INTELLIGENCE.


**Advanced man/machine interface**, which constantly **monitors the performance of the machine** and communicates **each diagnosis** to the operator via a large and detailed LCD screen in the dashboard.




LAYOUT A



LAYOUT B



SETTINGS



ENGINE ERROR



# 4.63H

**VENIERI STYLE.  
TOP LEVEL  
EFFICIENCY AND FUNCTIONALITY.**

Venieri Design Lab has redesigned the new cabin of 4.63H following the ambition to grant the best mix of **Italian style, design** and **functionality** even in a middle size loader range.

The **"Venierization"** of the interiors include the **yellow components** like a "nice to have" during your daily working process. Thanks to the new **Human/Machine interface** included in the **intuitive LCD** display, you can have a smart and constant control over the machine performances, **always connected to your Venieri**.






The brand new column steering system include the patented **adjustment control**, in order to fit exactly working/driving modes.



## BE COOL.

The entire ventilation system has been redesigned according to **ISO10263** also ensuring easy maintenance to the heating and A/C unit. Using a single dashboard, the operator can choose the ideal temperature, ensuring **maximum working comfort**. The 5.63C and 4.63H can be equipped with **Venieri Climatronic**.



## THE BLACK BOX.

For the first time on a Venieri cabin, all electronic controls are positioned in a **waterproof** position accessible only from inside the cabin, easy to access and complete all diagnostics.

(Photo: 5.63C)

## ENJOY THE SHOW.

The driver's seat is equipped with the **most advanced solutions in terms of comfort** for maximum operational efficiency.





# CLASS EVOLUTION.


## CLEAN POWER, ZERO CONSUMPTION. NEW DEUTZ STAGE IIIB/TIER IVf ENGINES

The engine that equips the 5.63C is the **new Deutz TD 2.9 L4**, a four cylinder unit of **178 in<sup>3</sup>** awarded as **best engine in his class**. The impressive performance, reliability and durability distinguishing this engine have been made possible by adopting the most advanced technology, such as: **external exhaust gas recirculation, electronically controlled Common Rail injection with 23,206 psi of pressure, turbocharger and wastegate valve**, and much more for a minimum specific consumption of **just 0.5 lbs /kWh**, - an outstanding figure for an engine of this size - which, through the use of an external gas recirculation system and the diesel oxidation catalyst (**DOC**) compliance with the **Tier 4f** emissions regulations and achieved.



### 5.63C

**Deutz TD 2.9 L4**  
58 kW - 79 HP



## JAPANESE TECHNOLOGY YANMAR ENGINE STAGE V/TIER IVf


The engine that equips the 4.63H is the **new Yanmar 4TNV98C**, a four cylinder unit of **203 in<sup>3</sup>** with **EGR system (Exhaust Gas Recirculation)** and **Diesel Particulate Filter DPF**; this has the peculiarity to operate without additives by capturing the fine dust of the exhaust gases and burning them during the automatic regeneration process, **keeping the filter clean** and keeping operating costs down. The DPF can work in three different modes: **assist regeneration, active regeneration, stationary regeneration**.

The Yanmar engine is equipped with a **Common Rail electronic injection system**, that grant an accurate control of the injection and combined with the exhaust treatment system, ensures **low fuel consumption** and reduces pollutant emissions.



### 4.63H

**Yanmar 4TNV98C**  
53 kW - 72 HP



# Venieri GLOBAL

## CONTROL YOUR FLEET

**Venieri GLOBAL™** is our brand-new satellite monitoring system, which guarantees an increase in productivity by providing detailed information about the fleet and attachments, as well as an incredible amount of data to ensure the highest performance levels and greater economic efficiency.


### A V A I L A B L E F E A T U R E S

Machine localisation	✓	Work shifts alarm	✓
Alerts history	✓	Standard operating procedure history	0
Maintenance plan	✓	Energy-saving guidelines history	0
Maintenance history	✓	Location log	✓
Load information	✓	(map with locations and operating procedures)	✓
Working hours	✓	Information about diesel particulate filter	✓
Security control (engine block)	0	Geo-fencing	✓
Fuel consumption (total and partial)	✓	Localisation and managment fleet	✓
Fuel consumption while working	✓	Multiuser control with specific access policies	✓
Machine efficiency (while working)	✓	List of "sleeping" machines	✓
Detailed working hours	✓	Sms/e-mail notification	✓
Motion sensor alarm	✓	Anti-theft alarm	✓
Curfew alarm setting	✓	Parameters setting upon request	0


✓ Standad    0 Optional    X Not available

REPORTISTICA: CONSUMO CARBURANTE  
DA: 11/10/2018 00:00:00 - A: 11/10/2018

#### PRODUCTIVITY REPORT



FLEET CONTROL



APP FOR SMARTPHONE  
iOS™ AND ANDROID™





# BASIC MACHINE



Battery main switch	•	•
Tool box	•	•
Fuel preheating (cold climates)	0	0
Plugs with keys for fuel and hydraulic tanks	•	•
Proportional self lock front differential	•	•
Proportional self lock rear differential	0	0
Differential lock 100% engageable in front axle	0	0
Trailer coupling	•	•
Warning beacon	•	•
Soundproofing	•	•
Spare parts catalogue	•	•
User manual	•	•
Type-approval for road traffic	•	•
Safety clamp for bucket and lifting cylinders	•	•
Autolevelling ground level for bucket	•	•
Speed reduction kit	0	0
"Venieri GLOBAL" system	0	0
Double-speed hydraulic fan	•	•
Reversible fan (for radiator cleaning)	0	0
Hydraulic negative parking brake	0	•
Service brake on both axles with separate circuits	0	•
Inch pedal integrated in brake pedal	0	0
Greasing points grouped on the frame	•	•
Automatic centralized greasing system	0	0
Ride control	0	0
Engine preheating system	0	0
Environmentally-friendly hydraulic oil	0	0
Hydraulic oil ISO 46 (cold climates)	0	0
Cyclone dust separator	0	•
High speed Kit	0	-

# CABIN EQUIPMENT



ROPS/FOPS 2nd Level, pressurized and soundproofed	•	•
Front and rear windscreen wiper with washer	•	•
Halogen work lights (4 front + 2 rear)	•	•
LED work lights (4 front + 2 rear)	0	0
Mobile phone compartment	•	•
Bottle holder	•	•
Document compartment	•	•
Seat with mechanical suspension	•	•
Seat with pneumatic suspension	0	0
Seat with pneumatic suspension and heating	0	0
Seat armrests	•	•
Buzzer	•	•
Cabin carpet	•	•
Clothes hangers	•	•
Radio preparation	•	•
Supplementary socket 12V	•	•
Manual Air Conditioning	0	0
"Climatronic Venieri" system	0	0
Ceiling lamp	•	•
Sun visor	•	•
Rear view mirrors	•	•
Heatable rear view mirrors	0	0
First-aid kit	0	0
Fire extinguisher 4.41 lbs	0	0
Seat belt	•	•
Instrumentation and dashboard with LCD display	•	•
Safety glass breaker	•	•

# SPECIAL EQUIPMENT



Hydraulic or mechanical quick coupler	0	0
Cement mixing bucket	0	0
Multipurpose bucket (4 in 1)	0	0
Lifting forks	0	0
Asphalt and cement planer	0	0
Snow blower	0	0
Snow blade and "V" type snow blade	0	0
Angle-tilt dozer blade	0	0
Hand operating hammer	0	0
Polishing brush	0	0
Trencher	0	0
High tip bucket	0	0
High flow kit	0	0
Unpressurized return pipe	0	0
Double auxiliary line	0	0
Rear hydraulic line (single effect)	0	0



**VENIERI**

Via Piratello, 106 - 48022 Lugo (RA) ITALY  
 Tel. +39 0545 904411 - Fax +39 0545 30389  
 e-mail: [info@vf-venieri.com](mailto:info@vf-venieri.com)  
[www.vf-venieri.com](http://www.vf-venieri.com)

The illustrations on the present folder do not necessarily show the product standard version. Data and dimensions described in this folder are not binding. Venieri reserves the right of carrying out possible changes at any time and without previous notice because of its policy of steady development and improvement of the products.